



Chef Display Hub

Wireless Temperature Display & Alert Unit

P/N	TP2650	Model No.	CHEF1
-----	--------	-----------	-------

Overview & Features



- Magnetically attaches to an oven and charger. A 430SS adhesive plate can be provided if the surface is non-magnetic.
- Rechargeable Li-Ion battery creates a run time of 12 hours.
- Displays two temperatures, incorporates a bright multi-color LED status light, and has a piezo audio alarm.
- One button switch on the rear face turns unit on/off and cancels the alarm.
- Incorporates a BLE radio to listen for temperature data coming from the temperature probes, and a Wi-Fi radio for connectivity to view live data and archive records.
- Non-volatile memory can back up data for 24 hours in the event of loss of connectivity.
- Charging is via the Charging Tree or Small System Charger.
- Auto-Pairs to Probes to avoid entering probe serial numbers
- Line Powered Option available. Consult factory.

Materials

ASA, polyester, and stainless-steel charging contacts.

Environmental & Hazardous Materials

RoHS, REACH

Specifications

Size	95 x 82 x 22 mm (3.75 x 3.25 x 0.88 in)
Weight	126 g (4.4 oz)
Battery Life	12 hours (rechargeable Li-Ion)
Connectivity	BLE (probe listening) and Wi-Fi (live data / archive)
Data Backup	Non-volatile memory, 24-hour buffer on loss of connectivity
Charging	Charging Tree or Small System Charger